

29/67-68 Moo 7 Srinakarin Road, Teparuk, Muang, Samutprakarn 10270

Tel: +662 - 383-5473 Fax: +662 - 383 - 5474

### **ANTIFOAM HD-30**

ANTIFOAM HD-30 is a milky white emulsion of low viscosity. It is an excellent defoamer for aqueous solution, which is diluted 15 – 20 times when it is used. The features of ANTIFOAM HD-30 include the following.

- 1. It has content defoaming effect and practically all the foams are removed when a small amount of ANTIFOAM HD-30 is added.
- 2. It can be well dispersed and can be dissolved event in almost all kinds of aqueous solution. It excels in dilution stability.
- 3. It has such good heat stability that it can be used for aqueous solution at elevated temperatures or for high temperatures disinfectant solution. Because of these characteristic features, ANTIFOAM HD-30 is suitable for sewage disposal, paper-manufacturing process, dyestuff making industries etc.

## **Typical properties:**

Appearance: White emulsion

Specific Gravity at 25 C: 1.01 - 1.05

Solid content (%): 10 + 1 Ionic property: Weak anionic

Dilute: Water

#### How to use:

- 1. Being an aqueous emulsion, it is recommended to dilute ANTIFOAM HD-30 15-20 times with water when used.
- 2. The amount of ANTIFOAM HD-30 to be used varies according to the kinds of foams and fluids. However, the proper amount of this agent for general purpose use is 0.005 0.05 of the total amount of a fluid for which ANTIFOAM HD-30 used
- 3. As for the methods of use, diluted ANTIFOAM HD-30 should be added to a fluid before foaming, or it should be added to a fluid in drops or sprayed as foams are made. The best way is to add a part of this defoamer before foaming, and thon add the remaining amount as foams are made.

## **Application:**

- 1. In the paper and pulp industry.
- 2. In the dyeing process in the dyestuff manufacturing industry.
- 3. At sewage treatment plant.
- 4. In addition, it can be used for removing foams in cutting oils, detergents, natural and synthetic latex, synthetic resin suspension etc.



# Future Chem Asia Co., Ltd.

29/67-68~Moo7 Srinakarin Road, Teparuk, Muang, Samut<br/>prakarn10270

Tel: +662 - 383-5473 Fax: +662 - 383 - 5474